

DATASHEET

FTTH IP65 Connectionbox for 4fiber, 2adapter and Fiber overlength box



General data

Application:

Optical Telecommunication Networks
 LAN, Optical fiber Communication Network
 CATV Networks
 FTTH access Network
 PON, G-PON

Configuration in LC with duplex adapters for 4 ports/ fibers

Configuration in SC with simplex adapters for 2 ports/ fibers

Delivery unassembled (**Crimp splice holder (12 splices)**, shrink splice holder (max. 4 splices double layed), 2x shrink protection and material for wall mounting included)

Technical properties

Cable entry without cable gland	1x max. 10mm / 2x max. 4mm
Cable sheath support	True
Colour	white
Dimensions	165x100x30 mm

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

FTTH IP65 Connectionbox for 4fiber, 2adapter and Fiber overlength box

Foreign body and contact protection	Protection against ingrees of dust
Hinged splice cassette	True
Holder for gas blocker	False
Holder for splitter	False
IP Protection	IP65
Material	Plastic
Max. Assembly (Adapter)	2
Mounting method	Wall mounting
Number of Fibres	4
Operating Temperature	-25 - 70 °C
Possibility of mast mounting	False
Scope of application	Outdoor
Suitable for adapter	SC Simplex/LC Duplex/E2000®
Type of Splice protection	Crimp & Thermo
UV-resistant	True
Water protection	Protection against jet water
With Fiber overlength cassette	True

Available variants

ArtNr.	Bezeichnung	Access Control
FTTH-BOX-OUT-4	FTTH IP65 Connectionbox for 4fiber, 2adapter and Fiber overlength box	Special screw/ Seal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

