

DATASHEET

FTTH IP65 Connectionbox for 144 fiber and Fiber over-length box



General data

Application:

Optical Telecommunication Networks
LAN, Optical fiber Communication Network
CATV Networks
FTTH access Network
PON, G-PON

Delivery unassembled (shrink splice holder, shrink protection and material for wall mounting included)

Technical properties

Cable entry without cable gland	16 x 2-3mm
Cable sheath support	True
Colour	grey
Dimensions	232 x 358.5 x 130.5 mm
Foreign body and contact protection	Protection against ingresses of dust
Hinged splice cassette	True
Holder for gas blocker	True

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.

DATASHEET

FTTH IP65 Connectionbox for 144 fiber and Fiber over-length box

Holder for splitter	True
IP Protection	IP65
Material	Plastic
Mounting method	Wall mounting
Number of Fibres	144
Operating Temperature	-25 - 70 °C
Possibility of mast mounting	True
Scope of application	Outdoor
Type of Splice protection	Thermo
UV-resistant	True
Water protection	Protection against jet water
With Fiber overlength cassette	True

Available variants

ArtNr.	Bezeichnung	Access Control
FTTH-BOX-OUT-7	FTTH IP65 Connectionbox for 144 fiber and Fiber overlength box	Special screw/ Seal

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 05-09-2026 . Technical changes reserved.

