

DATASHEET

26-Port Web Managed GE PoE+ Switch, 2x SFP/RJ45 Combo, (185W)



General data

24 PoE-Plus Gigabit Ethernet ports and 2 Gigabit SFP slots
 QoS control for traffic prioritization and bandwidth management
 DHCP Client/Server
 Supports IPv4/IPv6 network operation
 Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)
 IEEE 802.1d/w/s Spanning Tree Protocol (STP) and port mirroring
 IP Multicast Filtering through IGMP Snooping V1 / V2 / V3
 Supports port-based VLAN, IEEE 802.1Q VLAN Tagging
 IEEE 802.3ad LACP for auto port aggregation

Technical properties

10 Gigabit Ethernet	False
Depth	211.0 mm
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True
Height	44.0 mm

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



DATASHEET

26-Port Web Managed GE PoE+ Switch, 2x SFP/RJ45 Combo, (185W)

Manageable	True
Manufacturer	LevelOne
Max. PoE per Port	30 W
Mounting method	482.6 mm (19 inch) mounting
Number of combination-ports RJ45/Mini GBIC	2
Number of ports 10/100/1000 Mbps RJ45	24
Number of ports PoE	24
Power over Ethernet (PoE)	802.3 at (PoE+)
Width	442.0 mm

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GEP-2651	26-Port Web Managed GE PoE+ Switch, 2x SFP/RJ45 Combo, (185W)	185 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

