DATASHEET

26-Port L3 Lite Managed Gigabit PoE+ Switch, 24x PoE+, 370W, 2 x1G SFP/RJ45







General data

24 PoE+ Gigabit Ethernet Ports + 2 Gigabit Ethernet SFP/RJ45 Combo Slots
SFP Slots supports MiniGBICs for Gigabit 1000Base-X
IEEE-802.3af / at PoE compliance with PoE detection
PoE+ up to 30W pro Port
Max. PoE Power: 185W
QoS, VLAN, LACP, Port mirrowing, Autonegotiation and Auto MDI/MDIX
Management: SNMP, WEB, RMON
19“ Mounting brackets included
Metal housing (L x W x D): 442 x 211 x 44 mm

Technical properties

10 Gigabit Ethernet	False
Depth	211.0 mm
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True
Height	44.0 mm

This datasheet was created automatically on 23-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

26-Port L3 Lite Managed Gigabit PoE+ Switch, 24x PoE+, 370W, 2 x1G SFP/RJ45

Layer 2	True
Layer 3	True
Manageable	True
Manufacturer	LevelOne
Max. PoE per Port	30 W
Mounting method	482.6 mm (19 inch) mounting
Number of combination-ports RJ45/Mini GBIC	2
Number of ports 10/100/1000 Mbps RJ45	24
Number of ports PoE	24
Power over Ethernet (PoE)	802.3 at (PoE+)
Width	442.0 mm

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GEP-2682	26-Port L3 Lite Managed Gigabit PoE+ Switch, 24x PoE+, 370W, 2 x1G SFP/RJ45	370 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION