DATASHEET

Hilbert 18-Port Gigabit Smart Lite Switch,16 x Gigabit RJ45 2 x Gigabit SFP







General data

16 Gigabit Ethernet ports and 2 Gigabit SFP slots
Supports 8K MAC address auto-learning and auto-aging
9K jumbo frames to increase data transfer rates
IP multicast filtering through IGMP Snooping V1/V2
802.1Q tag-based VLAN enables network segmentation to improve performance and security
IEEE 802.1p QoS with 4 priority queues
Supports storm control for unknown unicast/broadcast/multicast
Minimizes carbon footprint with energy efficient technology (IEEE 802.3az)
4KV surge protection, 6KV contact/8KV air ESD protection
Web-based Smart Lite real-time management
Supports LevelOne IP Locator for easier IP management.

The LevelOne Hilbert GES-2118 Gigabit Smart Lite Switch is a latest generation Ethernet switch that combines performance, improved functionality and user-friendliness. It therefore enables particularly cost-efficient integration of Ethernet services in the business environment and for ambitious home users. The GES-2118 offers 16 (10M/100M/1G) full-fledged RJ45 ports, as well as 2 Gigabit SFP slots. With the new LevelOne IP Locator, the simple switch discovery software, all Hilbert series switches can be searched and information about the switch and IP configuration can be displayed. It is compatible with the most common Windows and Mac operating systems.

This datasheet was created automatically on 05-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Hilbert 18-Port Gigabit Smart Lite Switch,16 x Gigabit RJ45 2 x Gigabit SFP

The LevelOne GES-2118 offers high hardware performance and environmental flexibility for businesses. Additionally, the GES-2118 is ideal for easy management, optimal usability and lower total cost of ownership.

General
Color: Black

Features
L2 switching features
- IGMP snooping
- Link Aggregation (Supports static link aggregation)
- Port mirroring
- Cable Test

VLAN
- Supports up to 32 VLANs (out of 4K VLAN IDs)
- MTU/Port/802.1Q VLAN

Quality of Service (QoS)
- Support Port-based/802.1p/DSCP priority
- Support 4 priority queues
- Rate Limit
- Storm control

Administration
- Web-based Graphic User Interface (GUI)
- Supports LevelOne IP Locator for easier IP management.

Miscellaneous
Grade Commercial
Data rate Gigabit Ethernet
PoE Supported No
Manageable Yes
Fanless Yes
Concurrent ports 18.00 ports
Series HILBERT series
Non-disclosure
Embedded system SoC

Others
Approvals and Compliance
- CE
- UKCA
- FCC Part 15, Subpart B Class B
- RoHS

Operating humidity 10% RH ~ 90% RH

This datasheet was created automatically on 05-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Hilbert 18-Port Gigabit Smart Lite Switch,16 x Gigabit RJ45 2 x Gigabit SFP

Operating temperature 0°C ~ 45°C
Storage humidity 5% RH ~ 95% RH
Storage temperature -40°C ~ 70°C

scope of delivery
● GES-2118
● Power cord
● 19" Rack Mount Kit
● Quick Installation Guide
● Declaration of Conformity

performance
Switching capacity 36 Gbps

Physical Specifications
Product weight (kg) 1.08 kg
Dimensions (W x D x H) 271 x 181.5 x 44.5 mm

System specifications
Energy consumption 15 W
MTBF 43,800 hrs
Packet forwarding rate 26,784 Mpps
Heat dissipation 51.18 (Btu/H)
Port Configuration 18
Standards
● IEEE 802.3 10-BASE-T (Ethernet)
● IEEE 802.3u 100-BASE-TX (Fast Ethernet)
● IEEE 802.3ab 1000BASE-T (Gigabit Ethernet)
● IEEE 802.3z 1000BASE-X (Gigabit Ethernet)
● IEEE 802.3x Flow Control (full-duplex flow control)
● IEEE 802.3az: Energy Efficient Ethernet
Power supply 100-240 VAC, 50-60 Hz
Acoustic noise (dB) 0 dB (A)
Attachment 19" rack mount, desk mount
Flash memory size 2 MB
MAC address table 8K
Jumbo frames (KB) 9 K
Indicator Power, System, Link/Act
Packet buffer 4.1 Mbits

Technical properties	
10 Gigabit Ethernet	False
Ethernet	True
Fast Ethernet	True

This datasheet was created automatically on 05-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Hilbert 18-Port Gigabit Smart Lite Switch,16 x Gigabit RJ45 2 x Gigabit SFP

Gigabit Ethernet	True
Manageable	True
Manufacturer	LevelOne
Mounting method	482.6 mm (19 inch) mounting
Number of ports 10/100/1000 Mbps RJ45	16
Number of ports 1000 Mbps Mini GBIC	2

Available variants

ArtNr.	Bezeichnung	Unique
GES-2118	Hilbert 18-Port Gigabit Smart Lite Switch,16 x Gigabit RJ45 2 x Gigabit SFP	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION