

DATASHEET

28-Port L3 Lite Managed Gigabit PoE Switch, 24 PoE Outputs, 185W, 4x 10GbE SFP+



General data

24x Gigabit PoE Ports + 4x 10-Gigabit SFP+ slots

SFP+ slots support MiniGBICs for 10Gigabit 10GBaseX

PoE: IEEE-802.3af / at PoE compliance with PoE detection

IEEE-802.1d/w/s Spanning Tree Protocol (STP) and Port mirroring

Management: SNMP, WEB, RMON, Telnet and TFTP management

Features: IPv4/IPv6, port-based VLAN, IEEE 802.1Q VLAN-tagging and GVRP

IP Multicast Filtering with IGMP Snooping V1 / V2 / V3

L3 Features: Static Route, DHCP Server, ARP

Port-based IEEE-802.1X-authentication over access list (ACL) with over 512 entries

IEEE 802.3ad LACP for automatic port-aggregation

Metal housing (W x D x H): 442 x 221 x 44 mm

Technical properties

10 Gigabit Ethernet	True
Depth	442.0 mm
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

28-Port L3 Lite Managed Gigabit PoE Switch, 24 PoE Outputs, 185W, 4x 10GbE SFP+

Height	44.0 mm
Layer 2	True
Layer 3	True
Manageable	True
Manufacturer	LevelOne
Max. PoE per Port	30 W
Mounting method	482.6 mm (19 inch) mounting
Number of ports 10 Gbps Mini GBIC	4
Number of ports 10/100/1000 Mbps RJ45	24
Number of ports PoE	24
Operating Temperature	0 – 45 °C
Power over Ethernet (PoE)	802.3 at (PoE+)
Width	211.0 mm

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GTP-2881	28-Port L3 Lite Managed Gigabit PoE Switch, 24 PoE Outputs, 185W, 4x 10GbE SFP+	185 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.

