

DATASHEET

52-Port L3 Lite Managed Gigabit PoE Switch, 48x GE PoE + 4x 10G SFP+, 400W



General data

48 PoE+ Gigabit Ethernet Ports + 4x 10GE SFP+ Slots + 1x RJ45 Console Port

SFP+ Slots supports MiniGBICs for 10 Gigabit Ethernet

PoE: IEEE-802.3af / at PoE compliance with PoE detection

IEEE-802.1d/w/s Spanning Tree Protocol (STP) and Port mirroring

Management: SNMP, WEB, RMON, CoS, Telnet and TFTP management

Features: IPv4/IPv6, port-based VLAN, IEEE 802.1Q VLAN-tagging and GVRP

IP Multicast Filtering with IGMP Snooping V1 / V2 / V3

L3 Features: Static Route, Traceroute, DHCP Server, ARP

Port-based IEEE-802.1X-authentication over access list (ACL)

IEEE 802.3ad LACP for automatic port-aggregation

Metal housing (W x D x H):: 440 x 330 x 44.5 mm

Technical properties

10 Gigabit Ethernet	True
Depth	330.0 mm
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

52-Port L3 Lite Managed Gigabit PoE Switch, 48x GE PoE + 4x 10G SFP+, 400W

Height	44.5 mm
Layer 2	True
Layer 3	True
Manageable	True
Manufacturer	LevelOne
Mounting method	482.6 mm (19 inch) mounting
Number of Copper Ports	48
Number of Fiber Ports	4
Number of ports 10 Gbps Mini GBIC	4
Number of ports 10/100/1000 Mbps RJ45	48
Number of ports PoE	48
Operating Temperature	0 - 45 °C
Power over Ethernet (PoE)	802.3 at (PoE+)
Width	440.0 mm

Available variants

ArtNr.	Bezeichnung	Max. PoE power
GTP-5271	52-Port L3 Lite Managed Gigabit PoE Switch, 48x GE PoE + 4x 10G SFP+, 400W	400 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.

