

DATASHEET

HDMI fiber optic cable AOC active 8K60Hz 48 Gbit/s 20m
black comp. with HDMI 2.1



General data

AOC HDMI Fiber Cable 8K@60Hz - Professional-Grade AV Connectivity for Demanding Applications

This active HDMI fiber optic cable is purpose-built for professional AV environments that require uncompromised signal quality over long distances. Ideal for digital signage, conference rooms, broadcast studios, or high-end installations.

Key Features:

- **Lengths:** 10m, 20m, 30m
- **Resolution:** 8K@60Hz, 4K@120Hz
- **Standard:** compatible with HDMI 2.1 / 2.0 (backward compatible)
- **Bandwidth:** Up to 48 Gbps
- **Active Chipset:** Ensures reliable, interference-free transmission
- **Connectors:** Zinc alloy housing with gold-plated contacts

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.

DATASHEET

HDMI fiber optic cable AOC active 8K60Hz 48 Gbit/s 20m black comp. with HDMI 2.1

- **Labeling:** Laser-engraved "Source" and "Display" for correct orientation
- **Jacket:** Flexible, halogen-free TPE outer jacket
- **Color:** Black, with laser-marked 8K logo

Eco-Friendly Packaging:

Plastic-free cardboard box, recyclable and shipping-ready. Designed to reduce waste and simplify logistics.

Perfect for:

System integrators, AV rental companies, public sector tenders, project planning firms, installers, and B2B resellers.

Technical properties

3D	True
ARC	True
Backwards compatible	True
Bending radius (dynamic/static)	40 mm
CEC	True
Cable and plug compatibility	Ultra High-Speed HDMI
Cable set	False
Cable type (passive/active/optical)	active optical
Chip	True
Color depth	16-Bit
Compliant with	TV
Compressions technologies	DSC
Connection type connection 1	Stecker
Connection type connection 2	Stecker
Connector 1 angulation	180°
Connector 2 angulation	180°
Contact Plating	gold-plated
DSC	True
Dust cover	No
Enhanced Color	Deep Color
HDCP Version	HDCP 2.3
HDMI Power	True
HDMI certified	True
HDR	HDR10
HEC (Ethernet channel)	True

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

HDMI fiber optic cable AOC active 8K60Hz 48 Gbit/s 20m black comp. with HDMI 2.1

Halogenfree	True
Kink protection	True
MSA	False
MST	False
Material Connector Housing	Zinc Alloy
Material Inner Conductor	BC
Material jacket	TPE
Max. mating cycles	5000
Max. resolution	8K@60Hz
Model	Adapter
Number of poles connection 1	19
Number of poles connection 2	19
Number of shieldings	double
Operating temperature	-5 - 45 °C
PCIe Data transfer	False
Plug dimensions Side 1	19.5 x 11.8 x 52.8mm
Plug dimensions Side 2	19.5 x 11.8 x 52.8mm
Scope of delivery	1 x HDMI Cable
Shielded	True
Speed	48 Gbit/s
Supported audio formats	compressed Audio format (Dolby Digital, Dolby TrueHD, DTS, DTS-HD Master Audio, Dolby Atmos)
Supported video standards	8K UHD
Temperature	-20 - 70 °C
Tensile strength (short/long)	98,1 N
Type of connector connection 1	HDMI Type A
Type of connector connection 2	HDMI Type A
Type of packaging	paper box
Type of signal	Digital
VESA certified	False
VRR	True
Version	HDMI Version 2.1a
Warranty	36 months
With termination resistor	False
eARC	True

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

HDMI fiber optic cable AOC active 8K60Hz 48 Gbit/s 20m black comp. with HDMI 2.1

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
HDMI-21-00006	HDMI fiber optic cable AOC active 8K60Hz 48 Gbit/s 10m black comp. with HDMI 2.1	Black	10 m	4.7 mm	26AWG
HDMI-21-00007	HDMI fiber optic cable AOC active 8K60Hz 48 Gbit/s 20m black comp. with HDMI 2.1	Black	20 m	4.7 mm	26AWG
HDMI-21-00008	HDMI fiber optic cable AOC active 8K60Hz 48 Gbit/s 30m black comp. with HDMI 2.1	Black	30 m	4.7 mm	26AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.

