

# DATASHEET

## HDMI Switch, 4K@60Hz, 2-to-1 & 1-to-2 ABS, black, switch button



### General data

The bidirectional HDMI switch allows for flexible switching between two HDMI sources and one display, or one HDMI source and two displays. It supports HDMI signals up to 4K@60Hz and transmits video and audio for monitors, TVs, projectors, PCs, consoles, or media players. Switching is conveniently handled via a button on the device, allowing for a quick change between HDMI 1 and HDMI 2. In the "1 source to 2 displays" mode, output is switchable rather than simultaneous. The switch is a compact solution for presentation environments, meeting rooms, training rooms, and professional AV setups. The retail packaging is plastic-free and made from 100% recycled cardboard.

Product information for HDMI Switch, 4K@60Hz, 2-to-1 & 1-to-2:

**2-WAY HDMI SWITCH:** Connects either two source devices to one display or one source device to two displays.

**4K@60HZ VIDEO OUTPUT:** Supports HDMI signals up to 4K at 60 Hz for monitors, TVs, projectors, consoles, Blu-ray players, and PCs.

**AUDIO AND VIDEO TRANSMISSION:** Transmits video and audio via HDMI; suitable for entertainment, office, and presentation applications.

**PUSH-BUTTON SWITCHING:** Conveniently switch between HDMI 1 and HDMI 2 using the integrated switch button.

**BIDIRECTIONAL USE:** Supports both "2 sources to 1 display" and "1 source to 2 displays" configurations; When using

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

# DATASHEET

## HDMI Switch, 4K@60Hz, 2-to-1 & 1-to-2 ABS, black, switch button

one source with two displays, the output is not simultaneous but switchable.

**PLASTIC-FREE RETAIL PACKAGING:** Packaging made from 100% recycled cardboard, featuring a product image and description in 7 languages.

### KEY TECHNICAL SPECIFICATIONS:

- HDMI to 2x HDMI bidirectional video switch
- 2x HDMI: 4K/60 Hz
- Supports audio and video transmission
- Includes a switch button to toggle between HDMI 1 and HDMI 2
- Supports: 1x host to 2x monitors as well as 2x hosts to 1x monitor
- Chipset: AW3410S

| Technical properties          |         |
|-------------------------------|---------|
| Automatic alarm processing    | False   |
| Automatic sequence            | False   |
| Full screen at alarm          | False   |
| Max. resolution               | 4K@60Hz |
| OSD-programming               | False   |
| Suitable for 19 inch mounting | False   |
| Text generator                | False   |
| Video Inputs                  | HDMI    |
| Video interface               | HDMI    |
| Video loss function           | False   |
| With communication interface  | False   |
| With loop through function    | False   |

| Available variants |                                                                 |                         |                           |
|--------------------|-----------------------------------------------------------------|-------------------------|---------------------------|
| ArtNr.             | Bezeichnung                                                     | Number of camera inputs | Number of monitor outputs |
| HDMI-SWITCH-00001  | HDMI Switch, 4K@60Hz, 2-to-1 & 1-to-2 ABS, black, switch button | 2                       | 1                         |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 19-09-2026 . Technical changes reserved.

