DATASHEET

Power Supply 5 V, 2.4 A, 12 W, Mean Well



General data

Power supply unit for the top-hat rail for operating e.g. Industrial switching

plastic housing, step shape
1∅, full range input
compact size, 1SU ~ 6SU width (DIN EN43880)
insulation class II
adjustable DC output voltage
idle current consumption <0, 3W
Mount on industrial rails TS-35 / 7.5 or 15
Suitable for building automation and control of household appliances

Technical properties

1st secondary output voltage	5 V

Available variants

ArtNr.	Bezeichnung	Max. output current 1	Power output
HDR-15-5	Power Supply 5 V, 2.4 A, 12 W, Mean Well	2.4 A	12 W

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION