

# DATASHEET

## Industrial Media Converter, 1x 100/1000 SFP, 1x 100/1000T RJ45



### General data

Wide range of operation voltage 12 .. 48 V DC  
 Auto-MDI/MDI-X function  
 Dual Rate SFP Slot  
 Redundant power supply input  
 Temperature range -40°C .. +75°C  
 Rugged metal housing, EMV-secure, protection class IP30  
 DIN-Rail or wall mounting possible  
 Suitable DIN-Rail power supply: DR-15-24

### Technical properties

|                               |               |
|-------------------------------|---------------|
| Construction type             | Single device |
| Degree of protection          | IP30          |
| Depth                         | 110.0 mm      |
| Fast Ethernet                 | True          |
| Gigabit Ethernet              | True          |
| Height                        | 135.0 mm      |
| Managed                       | False         |
| Manufacturer                  | CTS           |
| Mode                          | MM or SM      |
| Power over Ethernet           | False         |
| Suitable for 19 inch mounting | False         |
| Width                         | 36.0 mm       |

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.



# DATASHEET

## Industrial Media Converter, 1x 100/1000 SFP, 1x 100/1000T RJ45

### Available variants

| ArtNr.   | Bezeichnung                                                    | Rail mounting possible |
|----------|----------------------------------------------------------------|------------------------|
| IAC-3012 | Industrial Media Converter, 1x 100/1000 SFP, 1x 100/1000T RJ45 | True                   |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

