DATASHEET

Industrial Media Converter, 2 x 100/1000 SFP, 2x 100/1000T RJ45



General data

Wide range of operation voltage 12 .. 48 V DC
Auto-MDI/MDI-X function
Dual Rate SFP Slot
Support for 3 different modes: Switch, Fiber Backup and Dual Media Converter mode
Redundant power supply input
Temperature range -40°C .. +75°C
Rugged metal housing, EMV-secure, protection class IP30
DIN-Rail or wall mounting possible
Suitable DIN-Rail power supply: HDR-15-24

Technical properties

Construction type	Single device
Degree of protection	IP30
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True
Layer 2	False
Managed	False
Manufacturer	CTS
Mode	MM or SM
Power over Ethernet	False
Suitable for 19 inch mounting	False

This datasheet was created automatically on 06-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Industrial Media Converter, 2 x 100/1000 SFP, 2x 100/1000T RJ45

Available variants		
ArtNr.	**Bezeichnung**	**Rail mounting possible**
IAC-3014	Industrial Media Converter, 2 x 100/1000 SFP, 2x 100/1000T RJ45	True

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION