

DATASHEET

Industrial Media Converter, 2 x 100/1000 SFP, 2x 100/1000T RJ45



General data

Wide range of operation voltage 12 .. 48 V DC
 Auto-MDI/MDI-X function
 Dual Rate SFP Slot
 Support for 3 different modes: Switch, Fiber Backup and Dual Media Converter mode
 Redundant power supply input
 Temperature range -40°C .. +75°C
 Rugged metal housing, EMV-secure, protection class IP30
 DIN-Rail or wall mounting possible
 Suitable DIN-Rail power supply: HDR-15-24

Technical properties

Construction type	Single device
Degree of protection	IP30
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True
Layer 2	False
Managed	False
Manufacturer	CTS
Mode	MM or SM
Power over Ethernet	False
Suitable for 19 inch mounting	False

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

DATASHEET

Industrial Media Converter, 2 x 100/1000 SFP, 2x 100/1000T RJ45

Available variants

ArtNr.	Bezeichnung	Rail mounting possible
IAC-3014	Industrial Media Converter, 2 x 100/1000 SFP, 2x 100/1000T RJ45	True

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

