

DATASHEET

Adapter - DisplayPort 1.2 male to HDMI female 15 cm



General data

- Connects a DisplayPort source to an HDMI monitor cable
- Provides a single high-quality signal to an HDMI - ideal for computer Mac
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Supports DisplayPort 1.2 signal
- Molded PVC boot

Connections

- 1x DisplayPort 20-pin male
- 1x HDMI 19-pin female
- Molded PVC
- Shielded

Signal: IN / OUT

- Input video signal: DisplayPort
- Maximum range Single Link: 4Kx2K
- Video Output: HDMI
- Input Connector: DisplayPort Male 20pin
- Output Connector Type: HDMI A female 19pin

Operating Frequency

This datasheet was created automatically on 06-09-2026 . Technical changes reserved.



DATASHEET

Adapter - DisplayPort 1.2 male to HDMI female 15 cm

- Vertical Frequency Range: 50 / 60Hz
- Video amplifier bandwidth up to 5.4Gbps

Resolutions (HDTV)

- 4Kx2K / 30HZ
- Supports 3D mode

Dimensions

- Length: 80 mm
- Width: 23 mm
- Height: 12 mm
- Cable length: 150 mm

Environmental Characteristics

- Operating Temperature: 0°C to +70°C
- Operating humidity: 10% to 85% (non-condensing)
- Storage temperature: -10°C to +80°C
- Storage Humidity: 5% to 90% (non-condensing)

Power Requirements

- No need for external power supply
- Power Consumption (Max) 1W

Standards and Certifications

- DisplayPort 1.2
- EC
- RoHS
- WEEE

Package Contents

- 1x Adapter DisplayPort (Thunderbolt) to HDMI
- 1x Instruction Manual

Technical properties

Available variants

ArtNr.	Bezeichnung	Unique
IADAP-DP-HDMIF2	Adapter - DisplayPort 1.2 male to HDMI female 15 cm	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 06-09-2026 . Technical changes reserved.

