

DATASHEET

Adapter HDMI (F) to DVI-D (F)



General data

- HDMI 19-pin Male to DVI-D 24 + 1 Dual Link Female
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Provides up to 5 Gbps of bandwidth
- PVC coating die

Contacts

- Gold Plated
- PVC coated cast
- Shielded

Specifications

- Inner conductor: AWG 28
- 7-wire (5 cm)
- Shielded
- Current rating: 5 A DC
- Voltage: 300 V DC
- Insulation resistance: 5 MOhm
- Resistance of conductors: 2 Ohm
- Temperature-resistant plastic coating

Dimensions

- 40.2 x 64.0 x 15.2 mm (W x D x H)

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.



DATASHEET

Adapter HDMI (F) to DVI-D (F)

Certifications

- UL 1007
- 9002
- UK

Package Contents

- 1x Adapter HDMI (F) to DVI-D (F)

Technical properties

Connection 1	HDMI (HDMI-A)
Connection 2	DVI-D 24+1
Connection type connection 1	jack
Connection type connection 2	Jack

Available variants

ArtNr.	Bezeichnung	Colour
IADAP-HDMI-644	Adapter HDMI (F) to DVI-D (F)	black

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

