DATASHEET

Adapter HDMI (F) to DVI-D (F)









General data

- HDMI 19-pin Male to DVI-D 24 + 1 Dual Link Female
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Provides up to 5 Gbps of bandwidth
- PVC coating die

Contacts

- Gold Plated
- PVC coated cast
- Shielded

Specifications

- Inner conductor: AWG 28
- 7-wire (5 cm)
- Shielded
- Current rating: 5 A DC
- Voltage: 300 V DC
- Insulation resistance: 5 MOhm
- Resistance of conductors: 2 Ohm
- Temperature-resistant plastic coating

Dimensions

- 40.2 x 64.0 x 15.2 mm (W x D x H)

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Adapter HDMI (F) to DVI-D (F)

Certifications
- UL 1007
- 9002
- UK

Package Contents
- 1x Adapter HDMI (F) to DVI-D (F)

Technical properties	
Connection 1	HDMI (HDMI-A)
Connection 2	DVI-D 24+1
Connection type connection 1	jack
Connection type connection 2	jack

Available variants

ArtNr.	Bezeichnung	Colour
IADAP-HDMI-644	Adapter HDMI (F) to DVI-D (F)	black

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION