

DATASHEET

Adapter HDMI (F) to DVI-D (M)



General data

- HDMI 19-pin female to DVI-D 18 + 1 male single link
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- PVC coating die

Contacts

- 1 x HDMI 19-pin female
- 1 x DVI-D 18 + 1 Pin Male
- Nickel plated
- PVC coated cast
- Shielded

Internal Specifications

- 28 AWG connectors
- 7-wire (5 cm)
- Shielded
- Current rating: 5A DC
- Voltage: 300 V DC
- Insulation resistance: 5 Mohms
- Resistance of conductors: 2 Ohms
- Temperature-resistant plastic coating

This datasheet was created automatically on 15-10-2026 . Technical changes reserved.



DATASHEET

Adapter HDMI (F) to DVI-D (M)

Dimensions

- 40.2 mm x 50.8 mm x 15.2 mm (W x D x H)

Certifications

- UL 1007, 9002, UK

Approvals

UL 20276, ISO9002, UK

Package Contents

- 1x Adapter HDMI M to DVI-D 18 + 1 M

Technical properties

Connection 1	HDMI (HDMI-A)
Connection 1 angle	180°
Connection 2	DVI-D 18+1
Connection 2 angle	180°
Connection type connection 1	jack
Connection type connection 2	Plug
Dust cover	false
Type of housing	Plastic
screened	True

Available variants

ArtNr.	Bezeichnung	Colour
IADAP-HDMI-651	Adapter HDMI (F) to DVI-D (M)	Black

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 15-10-2026 . Technical changes reserved.

