

DATASHEET

Adapter HDMI (F) to HDMI (F)



General data

Enables the connection for HDMI-cable to a screen

Connections

- HDMI 19-pin female
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Provides up to 5 Gbps of bandwidth
- PVC coating die

Contacts

- Nickel-plated
- PVC coated cast
- Shielded

Internal specifications

- Inner conductor: AWG 30
- 7-wire (50 mm)
- Current rating: .5 A DC
- Voltage: 300 V DC
- Insulation resistance: 50 MOhm
- Resistance of conductors: 2 Ohm
- Plastic coating resistant to temperature

Dimensions

- 40.2 x 50.8 x 15.2 mm (L x W x H)

Certifications

- UL 1007
- ISO9002
- RU
- CE

Package Contents

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.



DATASHEET

Adapter HDMI (F) to HDMI (F)

- 1x Adapter HDMI F / F

Technical properties

Connection 1	HDMI (HDMI-A)
Connection 2	HDMI (HDMI-A)
Connection type connection 1	jack
Connection type connection 2	jack
screened	True

Available variants

ArtNr.	Bezeichnung	Colour
IADAP-HDMI-F/F	Adapter HDMI (F) to HDMI (F)	black

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 01-11-2026 . Technical changes reserved.

