

DATASHEET

Converter - Mini-DisplayPort to HDMI, FullHD



General data

- Connects a source Mini DisplayPort M (Thunderbolt) to HDMI F via cable
- Provides a high-quality signal to the HDMI monitor - ideal for Mac
- Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
- Molded PVC boot

Standards and Certifications

- UL
- DisplayPort 1.1

Connections

- 1x Mini-DisplayPort 20-pin male (Thunderbolt)
- 1x HDMI A female 19-pin
- Contact material: Nickel-plated

This datasheet was created automatically on 06-09-2026 . Technical changes reserved.



DATASHEET

Converter - Mini-DisplayPort to HDMI, FullHD

Cable

- Inner conductor: AWG 30
- Shielded by foil and braiding
- Withstanding voltage: 300V DC
- Insulation resistance: 5 MOhm
- Conductive resistance: 10 Ohm
- Length: 150 mm
- Weight: 28 g

Package Contents

- 1x Adapter Mini-DisplayPort (Thunderbolt) to HDMI

Technical properties

Available variants

ArtNr.	Bezeichnung	Colour
IADAP-MDP-HDMIF	Converter - Mini-DisplayPort to HDMI, FullHD	white

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 06-09-2026 . Technical changes reserved.

