DATASHEET

USB-C to 2x HDMI 4K Adapter, 0.15m, black, iOS, Linux, Win11









General data

The USB-C™ to Dual HDMI Adapter can connect one USB-C™ port to two HDMI displays
When working with a single HDMI port, the resolution is up to 4K@60Hz (3840X2160P@60Hz)
When both HDMI ports are working, the maximum supported resolution is limited to 4K@30Hz
This USB-C™ to HDMI adapter is backwards compatible with 60Hz for 2K/1080P resolutions

Note: If you want to get 4K resolution, make sure your device supports 4K and uses an HDMI 2.0 or higher cable

Technical specifications
Supported standards: DisplayPort v1.4, DisplayPort v1.1a, HDMI2.0b/1.4b, VESA DDM standards, HDCP v2.2, DisplayID and EDID v1.4
Supports HDMI v2.0b output ports
Supports dual HDMI 4K@30Hz (MST)
Supports UHD video resolutions up to 4k@60 4:4:4 for single display
Supports EDID, MCCS
Interlaced High Dynamic Range (HDR) video and 3D video
RGB, YCbCr444, YCbCr422, YCbCr420
1-32 channels of LPCM audio including HBR audio compliant with IEC 61937 compressed audio
SST or up to 8 MST streams

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

USB-C to 2x HDMI 4K Adapter, 0.15m, black, iOS, Linux, Win11

HDR (High Dynamic Range) video
No external power supply is required for this USB-C™ to HDMI adapter, just plug and play and no drivers are needed

Compatibility
Linux
Windows
Mac OS
Android

Converter dimensions
Length: 64.5 mm
Width: 57.2 mm
Height: 12.0mm
Cable length: 15 cm

Package contents
IADAP USBC-HDMI2T4K USB-C™ to Dual HDMI Port Adapter
User Manual

Technical properties	
Connection type connection 1	Plug
Connection type connection 2	jack
Connection type connection 2b	jack
Connector 1 angulation	180°
Connector 2 angulation	180°
Max. resolution	4K@60Hz
Model	Adapter
Number of poles connection 1	24
Number of poles connection 2	19
Number of poles connection 2b	19
Scope of delivery	1 x USB-C Adabter
Supported video standards	4K UHD - Ultra High Definition
Type of connector connection 1	USB Type-C
Type of connector connection 2	HDMI Type A
Type of connector connection 2b	HDMI Type A

Available variants

ArtNr.	Bezeichnung	Colour	Length
IADAP-USBC-HDMI2T4K	USB-C to 2x HDMI 4K Adapter, 0.15m, black, iOS, Linux, Win11	black	0.15 m

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

USB-C to 2x HDMI 4K Adapter, 0.15m, black, iOS, Linux, Win11

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION