

DATASHEET

DisplayPort 1.4 Connection Cable, M/M 4K@120Hz, 1m
black, angled at one end



General data

DisplayPort 20-pin Male to DisplayPort 20-pin Male 90° Angled Cable

Compliant with DisplayPort 1.4 standards; Single shielded

Used for audio and video signal transfer; Supports 3D; With locking latches and gold-plated connectors

Resolution up to 4K / 120 Hz; Bandwidth: up to 32.4 Gbps

Technical properties

Connection type connection 1	Plug
Connection type connection 2	Plug
Connector 1 angulation	180°
Connector 2 angulation	90°
Dust cover	false
Kink protection	True
Max. resolution	4K@120Hz
Model	Round Cable
Number of poles connection 1	20
Number of poles connection 2	20
Number of shieldings	1

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

DisplayPort 1.4 Connection Cable, M/M 4K@120Hz, 1m black, angled at one end

Shielded	True
Speed	32.4 Gbit/s
Type of connector connection 1	DisplayPort (DP)
Type of connector connection 2	DisplayPort (DP)

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-DSP-A14-010NT9	DisplayPort 1.4 Connection Cable, M/M 4K@120Hz, 1m black, angled at one end	schwarz	1.0 m
ICOC-DSP-A14-020NT9	DisplayPort 1.4 Connection Cable, M/M 4K@120Hz, 2m black, angled at one end	schwarz	2.0 m
ICOC-DSP-A14-030NT9	DisplayPort 1.4 Connection Cable, M/M 4K@120Hz, 3m black, angled at one end	schwarz	3.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

