

DATASHEET

DisplayPort 1.1 to HDMI Connecting cable, black, 5 m



General data

- Converts the DisplayPort signal into a HDMI signal
- Provides a high quality digital video signal - ideal for the use of new sources with existing DisplayPort-/HDMI monitor
- Supports Deep Color as well as applications with bandwidth 10.8 Gbps and resolutions up to 1920x1200
- Integrated design for easy connection and eliminating cable clutter

Standards and Certifications

- UL 20276

Connections

- 1x DisplayPort 20-pin male
- 1x HDMI 19-pin male
- Material of contacts: nickel-plated
- Molded PVC boot with cable gland

This datasheet was created automatically on 06-10-2026 . Technical changes reserved.



DATASHEET

DisplayPort 1.1 to HDMI Connecting cable, black, 5 m

Cable

- Inner conductor: AWG 30
- Withstanding voltage: 300 V DC
- Shielded

General information

- Supports 8-bit and 10-bit Deep Color
- Bandwidth 10.8 Gbps
- Supports connection 1-lane, one-direction

Package Contents

- 1x Converter cable DisplayPort to HDMI

Technical properties

Connection type connection 1	Plug
Connection type connection 2	Plug
Connector 1 angulation	180°
Number of poles connection 1	20
Number of poles connection 2	19
Type of connector connection 1	DisplayPort (DP)
Type of connector connection 2	HDMI Type A

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-DSP-H-010	DisplayPort 1.1 to HDMI Connecting cable, black, 1 m	Black	1.0 m
ICOC-DSP-H-020	DisplayPort 1.1 to HDMI Connecting cable, black, 2 m	Black	2.0 m
ICOC-DSP-H-030	DisplayPort 1.1 to HDMI Connecting cable, black, 3 m	Black	3.0 m
ICOC-DSP-H-050	DisplayPort 1.1 to HDMI Connecting cable, black, 5 m	Black	5.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 06-10-2026 . Technical changes reserved.

