

DATASHEET

DisplayPort to VGA converter cable, black, 1.8 m



General data

- Easy connection of computers equipped with DisplayPort connector to VGA monitors, projectors etc.
- Provides a high-quality digital video signal - ideal for extending the life of the old devices with VGA connection
- Supports color depth, applications with high frequency band to 10.8 Gbps and resolutions up to 1080p monitor 1920 x 1200 (WUXGA)
- Integrated design for easy connection and eliminating cable clutter
- Plug and Play
- Compatible with Windows and Mac

Standards and Certifications

- UL 20276

Connections

- 1x DisplayPort 20-pin male
- 1x VGA 15-pin male
- Material: Nickel-plated
- Material of contacts: Gold-plated
- Molded PVC boot

Cable

- Inner conductor: AWG 28
- Withstanding voltage: 300 V DC
- Thermal plastic casing

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

DisplayPort to VGA converter cable, black, 1.8 m

- Shielded

General information

- Maximum single link range: 1920x1200, 1080P
- VGA resolution up to 1920x1200
- Frequency: 154 MHz / 144 MHz

Package Contents

- 1x Converter cable DisplayPort to VGA

Technical properties

Connection type connection 1	Stecker
Connection type connection 2	Stecker
Type of connector connection 1	DisplayPort (DP)
Type of connector connection 2	VGA DBHD15

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-DSP-V-018	DisplayPort to VGA converter cable, black, 1.8 m	Black	1.8 m
ICOC-DSP-V-030	DisplayPort to VGA converter cable, black, 3 m	Black	3.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.

