

DATASHEET

DVI-D Dual-Link Connecting cable M / M, with ferrite 2 m



General data

- This DVI cable allows the digital video transmission from PC to monitor
- Supports resolutions higher than Full HD 1080p (1920x1080) up to WQXGA (2560x1600)

Features

- Configuration: DVI-D Dual Link (24 + 1) male, DVI-D Dual Link (24 + 1) male
- Version with 2 ferrite cores
- With gold contacts
- With triple shielding: Foil + braid + PiMF
- Colour: Black

Package Contents

- 1x DVI digital (DVI-D) Dual Link with ferrite

Technical properties

Connection type connection 1	Plug
Connection type connection 2	Plug
Number of poles connection 1	25
Number of poles connection 2	25
Type of connector connection 1	DVI-D 24+1
Type of connector connection 2	DVI-D 24+1

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.



DATASHEET

DVI-D Dual-Link Connecting cable M / M, with ferrite 2 m

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-DVI-8100F	DVI-D Dual-Link Connecting cable M / M, with ferrite 2 m	black	2.0 m
ICOC-DVI-8115F	DVI-D Dual-Link Connecting cable M / M, with ferrite 15 m	black	15.0 m
ICOC-DVI-811CF	DVI-D Dual-Link Connecting cable M / M, with ferrite 10 m	black	10.0 m
ICOC-DVI-8120F	DVI-D Dual-Link Connecting cable M / M, with ferrite 20 m	black	20.0 m
ICOC-DVI-8130F	DVI-D Dual-Link Connecting cable M / M, with ferrite 3 m	black	3.0 m
ICOC-DVI-8150F	DVI-D Dual-Link Connecting cable M / M, with ferrite 5 m	black	5.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 16-09-2026 . Technical changes reserved.

