

DATASHEET

Mini-DisplayPort M to DisplayPort M Cable 4K 60Hz, White, 2m



General data

Provides mini-DisplayPort 20-pin male to DisplayPort 20-pin male connections
 Provides wide bandwidth, digital audio / video signals from monitors and peripherals equipped with Mini-DisplayPort and DisplayPort - up to 4K @ 60Hz resolution
 Fully shielded to reduce electromagnetic interference (EMI) and other sources of interference
 Plug and Play for box-to-box applications
 Die-cast PVC connector covers
 Connectors
 mini-DisplayPort 20-pin male
 20-pin male DisplayPort

Technical characteristics
 Gold-plated contacts
 Die-cast PVC
 With cable gland
 4K @ 60Hz resolution
 AWG 32
 OD 4.8mm

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

DATASHEET

Mini-DisplayPort M to DisplayPort M Cable 4K 60Hz, White, 2m

Package contents

Mini-DisplayPort to DisplayPort monitor cable

Technical properties

Connection type connection 1	Plug
Connection type connection 2	Plug
Number of poles connection 1	20
Number of poles connection 2	29
Type of connector connection 1	Mini DisplayPort (Mini DP)
Type of connector connection 2	DisplayPort (DP)

Available variants

ArtNr.	Bezeichnung	Colour	Length	AWG
ICOC-MDP-010T4K	Mini-DisplayPort M to DisplayPort M Cable 4K 60Hz, White, 1m	white	1.0 m	32
ICOC-MDP-020T4K	Mini-DisplayPort M to DisplayPort M Cable 4K 60Hz, White, 2m	white	2.0 m	32
ICOC-MDP-030T4K	Mini-DisplayPort M to DisplayPort M Cable 4K 60Hz, White, 3m	white	3.0 m	32

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 22-09-2026 . Technical changes reserved.

