

DATASHEET

USB4 Gen.3 Cable M Typ-C - M USB Typ-C Black 0.8 m



General data

The USB4 cable takes you to the next generation of USB connectivity, with data bandwidth up to 40Gbps, 8K video support, 100W / 3A power, and broad compatibility with legacy USB-C™ and Thunderbolt 3 standard

Features

USB-IF certified USB 4.0 cable has USB-C™ male / USB-C™ male connections with E-Mark chip. It is perfect for hubs, docking stations, eGPUs that use Thunderbolt 4 interfaces.

Works in two lanes with up to 40 Gbps data transfer (over certified cables), 8 times faster than standard USB-C™ cable.

Supports power delivery up to 100W (3A max). The data transfer rate varies depending on the port the cable is used with.

Supports single 8K (7680x4320) at 60Hz or dual 4K (3840x2160) at 60Hz resolution, providing a high quality viewing experience.

Thunderbolt 3 compatible

Backward compatible with USB 3.2, USB 3.1, USB 3.0, USB 2.0

Technical specifications

Connections: USB-C™ to USB-C™ cable

USB 4.0 standard

Data transfer: 40 Gbps

Maximum power: 100W (3A max)

This datasheet was created automatically on 27-09-2026 . Technical changes reserved.



DATASHEET

USB4 Gen.3 Cable M Typ-C - M USB Typ-C Black 0.8 m

Video display: single 8K or double 4K @ 60Hz
Colour: black

Package Contents
Black USB-C™ cable

Technical properties

Connection type connection 1	Stecker
Connection type connection 2	Stecker
Number of poles connection 1	24
Number of poles connection 2	24
Type of connector connection 1	USB Type-C
Type of connector connection 2	USB Type-C

Available variants

ArtNr.	Bezeichnung	Colour	Length
ICOC-MUSB40-CMCM08	USB4 Gen.3 Cable M Typ-C - M USB Typ-C Black 0.8 m	Black	0.8 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 27-09-2026 . Technical changes reserved.

