


DATASHEET

Techly USB-C male to USB-C male, short, flat FPC fast charging cable



General data

USB4 Gen3 cable, super flexible and durable with a data transfer speed of 40Gbps.

Connections: USB-C™ male to USB-C™ male; Connect your USB-C™ device with various USB-C™ chargers.

Featuring Gen 3 data transfer (up to 40Gbps) and QC fast charging, the ICOC USBC-FL-U4 is the perfect solution for charging your USB-C™ devices on the go. Connect your USB-C™ device with various USB-C™ chargers and the built-in E-mark chip automatically recognizes the voltage and current of your Type-C device, provides high-speed charging up to 100W (20V/5A) for USB-C™ devices.

Thanks to its flat, tangle-free design and length of only 12.4 cm, it can easily be placed in a pocket, purse or suitcase and taken on the go.

Technical specifications

USB4 Gen3 USB-C™ male to male flex cable

Length: 12.4cm

Data: 40Gbps

Current: PD 100W (20V/5A)

Integrated Cypress 2103 E-Mark chip

It supports 8K 60Hz resolution

Thunderbolt 3 compatible

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

DATASHEET

Techly USB-C male to USB-C male, short, flat FPC fast charging cable

Aluminum shell with flat TPE FPC (Flexible Printed Circuit Board)
Colour: Black

Certifications
EC
RoHS

Technical properties	
Connection 1	USB-C
Connection 2	USB-C
Connection type connection 1	Plug
Connection type connection 2	Plug
With terminal resistor	False

Available variants		
ArtNr.	Bezeichnung	Colour
ICOC-USBC-FL-U4	Techly USB-C male to USB-C male, short, flat FPC fast charging cable	schwarz

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

