

DATASHEET

HDMI Extender Cat.5e/6 120m



General data

- Allows you to easily extend the HDMI signal using Cat. 5e / 6 cables to extend transmission distances
- Real Time transmission makes the reproduction in real time unique without delay and compression that degrade the viewing experience
- Allows long distance transmission distances of 120 meters using a single network cable for real-time video transmission
- Compatible with Cat.5e / 6 cables it allows to easily manage different types of wiring according to the installation needs
- Supports video bandwidth up to 10.2Gbps
- Compliance with the HDCP standard ensures protection in the transmission of high-definition content and ensures quality reception
- Simple to install, no configuration is required
- Suitable for videoconferencing systems, training areas, monitoring applications and multimedia and entertainment applications

Features

- Plug and play, no installation required
- Uncompressed signal and zero latency
- Supports full HD 1080p @ 60Hz resolution
- Transmission distance up to 120m via Cat.6 cable, 100m via Cat.5e cable, 80m via Cat5 cable; with self-adjustment depending on the length of the cable used
- Supports IR pass-back allowing you to easily manage the source device remotely from the receiver's position

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

HDMI Extender Cat.5e/6 120m

- Kit consisting of transmitter and receiver, works in pairs

Specifications

- HDMI compliance: HDMI1.3
- HDCP compliance: HDCP1.4
- HDMI resolution: 720x576 @ 50Hz, 720x480 @ 60Hz, 1280x720 @ 60Hz, 1920x1080 @ 60Hz, 640x480 @ 60Hz, 800x600 @ 60Hz, 1024x768 @ 60Hz, 1280x800 @ 60Hz, 1280x1024 @ 60Hz, 1440x900 @ 60Hz, 1680x1050 @ 60Hz
- Supported audio format: stereo L / R audio
- Transfer rate: 10.2Gbps
- TMDS signal input and output: 0.5 ~ 1.5Vp-p (TMDS)
- DDC signal input and output: 5Vp-p (TTL)
- Input cable length: ≤8m (AWG24)
- Output cable length: ≤8m (AWG24)
- Distance supported: CAT5 80m; CAT5E 100m; CAT6 120m
- Voltage / current: DC5V / 1A
- Consumption: TX: 2W; RX: <2W
- Operating temperature: 0 ~ 60 °C
- Storage temperature: -10 ~ 70 °C
- Humidity (without condensation): 0 ~ 90%
- Dimensions (WxDxH): 69.57 x 58.80 x 16.10 mm
- Material: aluminum alloy
- Black colour
- Weight: TX: 70g; RX: 70g

- Certification EC, RoHS, WEEE

Package Contents

- 1x Transmitter (TX)
- 1x Receiver (RX)
- 2x DC 5V 1A power supply
- 1x IR Blaster extension
- 1x IR receiver extension
- 1x Instruction manual

Technical properties	
Max. resolution	1920 × 1080 (FullHD)
Suitable for 19 inch mounting	False
Video Inputs	HDMI
Video interface	HDMI
Video norm	Colour PAL

Available variants

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.



DATASHEET

HDMI Extender Cat.5e/6 120m

ArtNr.	Bezeichnung	Number of camera inputs	Number of monitor outputs
IDATA-EXT-E71	HDMI Extender Cat.5e/6 120m	1	1

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 20-09-2026 . Technical changes reserved.

