


DATASHEET

HDMI Extender/Splitter IP (120m)



General data

- Carry your HDMI signal up to 120 m using a network cable Cat. 6
- The local unit enables to share the data to several remote units, if it is connected to those remote units via a switching hub

Specifications

- Supports HDCP 1.2
- Resolution HDMI input: 480i / 60Hz, 480p / 60Hz, 576i / 50Hz, 576p / 50Hz, 720p / 50/60Hz, 1080i / 50/60Hz, 1080p / 50/60Hz
- Resolution HDMI output: 480p / 60Hz, 576p / 50Hz, 720p / 50/60Hz, 1080p / 50/60Hz
- Color Format Video Support: 24bit / 30bit Deep color / Deep color 36bit
- Supported audio format: DTS-HD / Dolby True-HD / LPCM 7.1 / DTS / Dolby-AC3 / DSD
- Maximum Transmission Speed: 10.2Gbps
- TMDS signal: 0.5-1.5Vp-p (TMDS)
- DDC Signal: 5Vp-p (TTL)
- Cable length input: ≤5m (High Speed HDMI Cable AWG26)
- Length of output cable: ≤5m (High Speed HDMI Cable AWG26)
- Connector Type: RJ45
- Interface: Cat. 5e / 6
- Transmission distance: up to 120m Cat. 6 cable (Cat. 5e up to 100m)
- Wiring Standard: TIA / EIA 568 B

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.



DATASHEET

HDMI Extender/Splitter IP (120m)

- Power supply: DC5V
- Power consumption: <3.6W
- Operating temperature: 0-55°C
- Storage temperature: -20 - 70°C (non-condensing)
- Dimensions (WxDxH): 5.7 x 10.6 x 2.6 cm

- Package Contents
- Transmitter
- Receiver
- 2x Power
- Instruction Manual

Technical properties

Available variants

ArtNr.	Bezeichnung	Unique
IDATA-EXTIP-373	HDMI Extender/Splitter IP (120m)	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 10-09-2026 . Technical changes reserved.

