DATASHEET

Audio Extractor 7.1 LPCM HDMI 4K UHD 3D











Audio Mode	Output HDMI	Optical	L/R
2CH	V	V	V
LPCM 5.1	V	V	V
LPCM 7.1	V		V
Bitstream 5.1	V	V	
Bitstream 7.1	V		





General data

IDATA HDMI-EA74K extracts the audio signal from the HDMI source and convert it to optical or analog multi-channel digital audio.
It allows you to easily send the HDMI video signal to a TV, projector or monitor, and send the signals to a HDMI audio system with 7 channels.

Features

- It extracts the audio signal from an HDMI source
- Supports HDMI audio sampling rates up to 192kHz
- Supports optical audio sampling rate S / PDIF audio up to 192kHz
- Supports 4 outputs 3.5 "multi-channel analog audio
- Allows 4Kx2K resolutions and 3D reproductions
- Meets HDMI, HDCP 1.2 and DVI 1.0
- Supports audio HDMI high-bit-rate (HBR)

This datasheet was created automatically on 03-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Audio Extractor 7.1 LPCM HDMI 4K UHD 3D

• No HDMI connections for receiving audio on analog and optical outputs
• Incoming and outgoing can use HDMI cables up to 15 meters in length 1080p 8bit resolution, or 10m to 1080p 12bit
• Supports audio feature EDID between LPCM 7.1CH, TV EDID (external) and Audio Bitstream
• Supports CEC bypass
• Black Colour

Technical Specifications
• Video bandwidth: 300Mbps / 9Gbps
• Input ports: 1 x HDMI
• Output Ports: 1 x HDMI, 1 x Optical, 4 x 3.5" Phone Jack
• HDMI Audio sampling frequency up to 192kHz
• SPDIF Optical Audio sampling frequency up to 192 kHz
• HDMI Audio format: LPCM 2 / 5.1 / 7.1CH, 5.1CH Dolby Digital 2 ~, ~ 2 5.1CH DTS, Dolby Digital Plus, Dolby TrueHD, and DTS-HD Master Audio
• Optical Format Audio: 2CH LPCM, Dolby Digital 5.1 CH 2 ~, ~ 2 and DTS 5.1CH
• Audio Format L / R: 4 x output Phone Jack format; 7.1 CH Analogue Audio
• Power supply included 5V 2A

Environmental Features
• Operating Temperature: 0 ° C ~ 40 ° C
• Storage Temperature: -20˚C ~ 60˚C

Dimensions
• Width: 95 mm
• Depth: 82 mm
• Height: 23 mm

Certifications
• EC
• FCC
• WEEE

Package Contents
• Audio Extractor IDATA HDMI-EA74K
• Power supply 5V 2A
• Information Sheet

Technical properties	
Connection type primary side	HDMI Type A
Connection type secondary side	1xHDMI, 1xOptical, 4x3.5mm
Service primary side	HDMI
Service secondary side	HDMI
Transmission rate	9 GBit/s

This datasheet was created automatically on 03-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Audio Extractor 7.1 LPCM HDMI 4K UHD 3D

Available variants		
ArtNr.	**Bezeichnung**	**Unique**
IDATA-HDMI-EA74K	Audio Extractor 7.1 LPCM HDMI 4K UHD 3D	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION