

DATASHEET

HDMI Splitter 4K, UHD, 3D, 2 way



General data

The splitter IDATA HDMI2-4K2 allows you to split the audio / video signal from an HDMI source such as a Blu-ray player, STB, DVD, PS3, etc. on two LCD monitors, projectors, or HD displays simultaneously.

Features

- 1 input, 2 HDMI 2.0 output
- Allows you to display the same image on two monitors at once
- It can extend the distance of 30m from the source and from the splitter to monitor up to 25 m
- Supports 3D
- Supports HDCP 1.4 and 2.2
- Supported Audio: standard audio, DSD (Direct Stream Digital) and HD (HBR) audio
- HDMI Supported Resolutions: 480i / 480p / 720p / 1080i / 1080p / 4Kx2K @ 24/25/30 / 60Hz
- Supports Full HD resolution up to 4K Ultra-HD
- Black Colour

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

HDMI Splitter 4K, UHD, 3D, 2 way

Environmental Features

- Operating temperature: -10 / 55 ° C
- Storage temperature: -20 / 70 ° C
- Relative humidity: 0/95% non-condensing

Dimensions

- Width 96 mm
- Depth 59 mm
- Height 17 mm
- Weight 98 g

Certifications

- EC
- FCC
- RoHS
- WEEE

Package Contents

- 1x HDMI 2.0 Splitter 2-way
- 1x 5V / 1A
- 1x Instruction Manual

Technical properties

Available variants

ArtNr.	Bezeichnung	Unique
IDATA-HDMI2-4K2	HDMI Splitter 4K, UHD, 3D, 2 way	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

