

DATASHEET

HDMI Splitter 4K, UHD, 3D, 4 way



General data

The splitter IDATA HDMI2-4K4 allows to quadruple the audio / video signal from an HDMI source such as a Blu-ray player, STB, DVD, PS3, etc. four LCD monitors, projectors, or HD displays simultaneously.

Features

- 1 input, 4 HDMI 2.0 output
- Allows you to display the same image on four monitors simultaneously
- It can extend the distance of 30m from the source and from the splitter to monitor up to 25 m
- Supports 3D
- Supports HDCP 2.2
- Supported Audio: Audio standard, DSD (Direct Stream Digital) and HD (HBR) audio
- Supports HDMI1.0 version, HDMI1.4, HDMI2.0
- Supports HDCP1.4 version, HDCP2.2
- HDMI Supported Resolutions: 480i, 480p, 756th, 756p, 720p, 1080i, 1080p, 4Kx2K @ 24/25/30 / 60Hz

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

HDMI Splitter 4K, UHD, 3D, 4 way

- Can be cascaded
- Black Colour

Environmental Features

- Operating temperature: -10 / 55 ° C
- Storage temperature: -20 / 70 ° C
- Relative humidity: 0/95% non-condensing

Dimensions

- Width 156 mm
- Depth 79 mm
- Height 17 mm
- Weight 205 g

Certifications

- EC
- FCC
- RoHS
- WEEE

Package Contents

- 1x HDMI 2.0 Splitter 4-way
- 1x 5V / 1A
- 1x Instruction Manual

Technical properties

Available variants

ArtNr.	Bezeichnung	Unique
IDATA-HDMI2-4K4	HDMI Splitter 4K, UHD, 3D, 4 way	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

