DATASHEET

Techly 4K 5in 1out HDMI 2.0b Switch HDR HDCP2.2 with Remote Control







General data

5in 1out switch, supports 5 HDMI ports to switch three HDMI sources to one display terminal by remote control or manual button
It supports LED display function and is suitable for computer, notebook, HD-DVD, SKY-STB, PS3, Xbox360 and other devices
Support HDMI 2.0b version 4Kx2K HDR version; Support 3D video format; It supports HDCP 2.2
Support manual and intelligent dual switching option; Status indicator, real-time understanding of the progress of each port
Plug and play; Includes remote control and USB cable

ATA HDMI2-4K5160B switch can support 5 HDMI ports to switch to one display terminal by remote control or manual button.
It supports LED display function and is suitable for computer, notebook, HD-DVD, SKY-STB, PS3, Xbox360 and other devices.

Product specifications
Easily switch between any five HDMI sources
Support HDMI 2.0b version 4Kx2K HDR version
Incoming video signal: 0.5-1.0VOLTSP.P

This datasheet was created automatically on 04-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Techly 4K 5in 1out HDMI 2.0b Switch HDR HDCP2.2 with Remote Control

Single input video signal: 4Kx2K @ 60Hz
Video Bandwidth: 18.5Gbps/600MHz
Supported resolutions: 480i, 480p, 576i, 576p, 720p, 1080p, 4Kx2K@60Hz

Features
Multiple HD input sources such as DVD, player, A/V receiver, set-top box
Supports video resolution up to 4Kx2K at 60Hz
Easy installation, high performance conversion chip, no splash screen, no jitter, no signal loss
Supports 3D video format
Supports HDMI 600MHz bandwidth, 18.5Gbps data bandwidth per channel (18.5Gbps data bandwidth for all channels)
Supports uncompressed audio such as PCM
Supports compressed digital audio such as DTS Digital, Dolby Digital
Supports HDCP 2.2
Support manual and intelligent dual switching option
Status indicator, real-time understanding of each port's progress
An HDMI 2.0 cable is required for 4K viewing
Plug and play
Power specifications
DC 5V ID interface
Power Requirements: 5V/1A
Certifications
EC
FCC
RoHS
Box Contents
HDMI2.0b 5in 1out 4K@60Hz switch
Remote control
USB cable
User Manual

Technical properties

Available variants

ArtNr.	Bezeichnung	Unique
IDATA-HDMI2-4K5160B	Techly 4K 5in 1out HDMI 2.0b Switch HDR HDCP2.2 with Remote Control	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 04-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION