

DATASHEET

Converter Cable USB 2.0 to Dsub9/RS-232, 1.5 m



General data

- Converter from a single USB port to a RS-232 port
- Easily connect serial modems, digital cameras, label printers, card readers, barcode readers, PDAs and digital organizers
- Windows compatible - Plug and Play
- Hot-swappable

Connectors

- 1x USB 2.0 port Type-A male
- 1x RS-232 port, 9-pin male

General information

- Transfer rate: up to 225 Kbps
- Powered by USB 2.0
- Over-current protection
- Chipset Prolific PL2303RA

System requirements

- USB 1.1 or 2.0 port
- Windows 98, ME, 2000, XP, Vista, 7, 8, 10 compatible

This datasheet was created automatically on 02-10-2026 . Technical changes reserved.



DATASHEET

Converter Cable USB 2.0 to Dsub9/RS-232, 1.5 m

Physical information

- Cable length: 1.5 m

Standards and Certifications

- EC
- FCC
- USB 1.0
- USB 1.1
- RoHS
- WEEE

Package Contents

- 1x Converter USB to RS-232
- 1x User manual

Technical properties

Chip	True
Connection type connection 1	Plug
Connection type connection 2	Plug
Connector 1 angulation	180°
Connector 2 angulation	180°
Dust cover	false
Kink protection	True
Model	Round Cable
Number of poles connection 2	4
Speed	225 kBit/s
Type of connector connection 1	USB-A
Type of connector connection 2	D-Sub

Available variants

ArtNr.	Bezeichnung	Colour	Length
IDATA-USB2-SER-1A	Converter Cable USB 2.0 to Dsub9/RS-232, 1.5 m	Black	1.5 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 02-10-2026 . Technical changes reserved.

