
DATASHEET

Converter USB 3.0 to VGA, 0,15 m









General data

This converter is useful for connecting an additional monitor, LCD or projector to a free USB 3.0 port of the PC or laptop. You can use up to 6 drives on your computer and connect one additional monitor to one converter. Supports a video resolution up to 1920 x 1080 for the picture of a broadcast TV.

Connectors

- Input: 1x USB 3.0 Type-A Male
- Output: 1x VGA Female
- Gold-plated contacts

Features

- Allows you to connect additional video devices (CRT / LCD monitor / projector) to your laptop or PC
- With a proper system, you can connect up to 6 converters to one computer
- Possible settings: extended display (one picture on two displays), mirror display (the same picture on two displays) and primacy display (one main display, one secondary display)
- Only minimal differences in performance between a directly connected screen and a screen connected through the USB 3.0 converter
- Color: White

Specifications

This datasheet was created automatically on 16-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Converter USB 3.0 to VGA, 0,15 m

- Supports USB 3.0 and USB 2.0 Super Speed
- Maximum video resolution up to 1920 x 1080
- Maximum transfer rate: 5 Gbps
- Built-in RAM 512 MB (SDRAM) or higher
- Supports deep color 16:32 Bit
- Maximum operating current: 400 mA
- Supports multi-function displays
- CPU: Intel / AMD Single Core 1.5 GHz or higher

Environmental Characteristics

- Operating Temperature: -15 - 50 °C
- Storage temperature: 0 - 70 °C

System Requirements

- Windows XP, Vista, 7, 8, 8.1, Mac OS 10.7
- PC with a free USB 3.0 (or 2.0) port
- Minimum 512 MB of RAM
- SVGA graphic card
- Minimum Free Space 30 MB HDD

Dimensions

- Width: 55.4 mm
- Depth: 38.0 mm
- Height: 15.0 mm
- Cable length: 1.5 m

Package Contents

- 1x Converter USB 3.0 to VGA
- 1x Instruction Manual with CD

Technical properties	
Connection type connection 1	Plug
Connection type connection 2	jack
Connector 1 angulation	180°
Connector 2 angulation	180°
Dust cover	false
Kink protection	True
Max. resolution	1920x1080
Number of poles connection 2	15
Operating temperature	-15 – 50 °C
Speed	5 Gbit/s
Temperature	0 – 70 °C
Type of connector connection 1	USB-A

This datasheet was created automatically on 16-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Converter USB 3.0 to VGA, 0,15 m

Type of connector connection 2	VGA DBHD15

Available variants

ArtNr.	Bezeichnung	Colour	Length
IDATA-USB3-SVGA	Converter USB 3.0 to VGA, 0,15 m	white	0.15 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION