

DATASHEET

5-Port Fast Ethernet Industrial Switch, DIN rail



General data

- Offers flexibility of 5 x 10/100BASE-TX ports
- 10/100 Mb/s, full/half duplex, auto-negotiation, auto-MDI/MDIX
- Supports 12 to 48 V power inputs DC Voltage
- Compliant with IEC61000-6-2 for industrial environments

Technical properties

Depth	70 mm
Ethernet	True
Height	110 mm
Layer 2	False
Layer 3	False
Layer 4	False
Layer 7	False
Manageable	False
Manufacturer	LevelOne
Mounting method	DIN rail (top hat rail)
Number of ports 10/100 Mbps RJ45	5
Operating Temperature	-10 - 60 °C
Width	26 mm

Available variants

ArtNr.	Bezeichnung	Unique
IES-0500	5-Port Fast Ethernet Industrial Switch, DIN rail	Unique

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

5-Port Fast Ethernet Industrial Switch, DIN rail

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

