

DATASHEET

Industrial Switch 4x 10/100/1000T, 1x 100/1000 SFP



General data

Wide range of operation voltage 12 .. 58 V DC
 Auto-MDI/MDI-X function
 Dual Rate SFP Slot
 Redundant power supply input
 Temperature range -40°C .. +75°C
 Rugged metal housing, EMV-secure, protection class IP30
 DIN-Rail or wall mounting possible
 Suitable DIN-Rail power supply: DR-15-24

Technical properties

Degree of protection	IP30
Depth	89.4 mm
Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True
Height	109.2 mm
Manufacturer	CTS
Mounting method	DIN rail (top hat rail)
Number of ports 10/100/1000 Mbps RJ45	4
Number of ports 100/1000 Mbps Mini GBIC	1
Operating Temperature	-40 - 75 °C
Width	29.1 mm

Available variants

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Industrial Switch 4x 10/100/1000T, 1x 100/1000 SFP

ArtNr.	Bezeichnung	Unique
IES-3005-F1	Industrial Switch 4x 10/100/1000T, 1x 100/1000 SFP	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

