

DATASHEET

10-Port L2 Man.Gigabit PoE Ind. Switch 802.3AT/AF/BT PoE, DIN Rail -40°C to 75°C



General data

8 Gigabit PoE ports and 2 Gigabit SFP slots
 Port 1&2 10/100/1000Base-T RJ45(IEEE 802.3bt) PoE 90W
 Ports 3 to 8 support IEEE 802.3at Power over Ethernet (PoE+)
 Compliant with IEEE802.3af/at/bt
 Supports L2 management, such as QoS, VLAN, MSTP, port management and PoE management
 Supports ERPS for Ring topologies
 6KV surge protection, 8KV contact /15KV air ESD protection
 Supports DIN rail, wall or desktop mounting
 Working temperature range from -40°C to 75°C

The LevelOne IGP-1061 Layer2 Managed Gigabit PoE Industrial Switch offers 8 PoE 10/100/1000Base-T ports and 2 Gigabit SFP ports to enable high-speed networks in mission-critical environments. With industrial standard DIN rail mounting and highly visible status LEDs, easy monitoring of port connection activity is possible. Additionally, the SFP slots support pluggable modules, allowing you to choose from a variety of transceivers. This switch is a Power Sourcing Equipment (PSE) and is fully compliant with the IEEE802.3af/at/bt PoE standard with a maximum power budget of 90W on port 1 and 2. It helps to dramatically reduce infrastructure cabling costs, as there is no need for electrical wiring and fewer UPSs are required.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

10-Port L2 Man.Gigabit PoE Ind. Switch 802.3AT/AF/BT PoE, DIN Rail -40°C to 75°C

General

Color: Black

Features

L2 Features:

1. Port configuration

- Auto negotiation
- Flow control
- Port Mirror
- Traffic statistics

2. Link Aggregation:

- Static link aggregation
- LACP
- Algorithm based on Source/Destination MAC
- Algorithm based on Source/Destination IP
- 8 groups
- 8 ports per group

3. MAC Table:

- Aging time
- Static MAC address
- Dynamic MAC address management

4. VLAN:

- 4K Active VLANs
- 4K VID
- 802.1Q Tag VLAN
- Port VLAN
- Protocol VLAN
- MAC VLAN
- Management VLAN
- Voice VLAN
- Q-in-Q

5.ACL:

- 64 ACLs
- L2, L3 and L4
- Time-based ACL

6. Spanning tree :

- 802.1D Spanning Tree Protocol (STP)
- 802.1w Rapid Spanning Tree Protocol (RSTP)
- 802.1s Multiple Spanning Tree Protocol (MSTP)

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

10-Port L2 Man.Gigabit PoE Ind. Switch 802.3AT/AF/BT PoE, DIN Rail -40°C to 75°C

- Loop Guard
- Root Guard
- TC-BPDU Guard
- BPDU Guard
- BPDU filters

7. Ring protocol:

- MSTP/EAPS/ERPS

8. Multicast:

- 256 groups
- IGMP v1/v2/v3
- Fast Leave
- Multicast VLAN
- Static Multicast
- Multicast filters
- IGMP Statistics
- MLD snooping

9. PoE management:

- Support total power consumption control
- Support single port PoE ON/OFF
- Support port output priority

10. QoS:

- 4 priority queues
- CoS port-based
- CoS 802.1p based
- CoS DSCP based
- Scheduling algorithms SP, WRR, SP+WRR
- Storm Control (Broadcast, Multicast, Unknown Unicast)
- Bandwidth control per port

Other features:

- DHCP relay
- DHCP client
- DHCP snooping
- DHCP option 82
- SNMP client
- BOOTP client

Maintenance:

- Ping and Tracert
- System log (local and remote)

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

10-Port L2 Man.Gigabit PoE Ind. Switch 802.3AT/AF/BT PoE, DIN Rail -40°C to 75°C

- Memory and CPU monitoring

Administration Management:

- SNMP v1/v2c/v3
- RMON 4 groups
- WEB (HTTP/HTTPS)
- CLI (Telnet, Console, SSHv1/v2)
- Firmware upgrade via console/web/TFTP
- Configuration backup/reload
- All possible configurations in the CLI must exist in the WEB interface
- LLDP

Security Security:

- Port Security
- MAC address filter
- ARP Association (Manual, ARP scanning, DHCP snooping)
up to 200 entries
- ARP Protection
- DoS (Denial of Service)
- Classification of packages based on: End.MAC, IP End, TCP / UDP Ports, Protocol Type
- 802.1x authentication (port-based and MAC-based)
- TACACS/TACACS+ authentication
- RADIUS Authentication
- DHCP filters
- Guest VLAN
- SSLv2/SSLv3/TLSv1
- SSHv1/SSHv2
- Restriction of WEB access based on: IP Address, And. MAC and Port
- Port isolation
- Local User Name Password Authentication (2 levels)
- Loopback detection

Miscellaneous

Grade industrial

Data rate Gigabit Ethernet

PoE Supported Yes

Manageable Yes

Fanless Yes

Concurrent ports 10.00 ports

PoE power budget 360.00 watts

Non-disclosure

Embedded system VxWorks

Others

Approvals and Compliance

- CE

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

10-Port L2 Man.Gigabit PoE Ind. Switch 802.3AT/AF/BT PoE, DIN Rail -40°C to 75°C

● RoHS

Operating humidity 0%RH ~ 95%RH

Operating temperature -40°C ~ 75°C

Storage humidity 0%RH ~ 95%RH

Storage temperature -40°C ~ 85°C

Scope of delivery

● IGP-1061

● Power Terminal Block

● Console Cable

● Din rail mount kit

● Quick Installation Guide

● Declaration of Conformity

Physical Specifications

Product weight (kg) 0.5

Dimensions (W x D x H) 165 x 115 x 50 mm

System specifications

power consumption

● 5W (without PoE)

● 380W (full loading PoE on)

MTBF 338,634 hrs

Port Configuration 8*10/100/1000 RJ-45(PoE), 2*1000 Mbps SFP

Standards

● IEEE 802.3 10-BASE-T, Ethernet

● IEEE 802.3u 100-BASE-TX, Fast Ethernet

● IEEE 802.3ab 1000Base-T Gigabit Ethernet

● IEEE 802.3z 1000Base-X Gigabit Ethernet

● IEEE802.3x Flow Control and Back Pressure

● IEEE802.3af

● IEEE802.3at

● IEEE802.3bt

Power supply input: DC 48~57V

Acoustic noise (dB) 0 dB

Pin assignment and polarity 1/2 (+), 3/6 (-)

Attachment desk mount, DIN rail mount

Flash memory size 128 MB

RAM size 1024 MB

MAC address table 8K

Jumbo frames (KB) 10 KB

indicator

● Power: Ed

● Act/Link : Green

● PoE : Yellow

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

10-Port L2 Man.Gigabit PoE Ind. Switch 802.3AT/AF/BT PoE, DIN Rail -40°C to 75°C

Packet buffer 1 Mbits
Backplane (Gbit/s) 20 Gbps

Technical properties

Ethernet	True
Fast Ethernet	True
Gigabit Ethernet	True
Manageable	True
Manufacturer	LevelOne
Mounting method	Desk type
Number of ports 10/100/1000 Mbps RJ45	8
Number of ports 1000 Mbps Mini GBIC	2
Power over Ethernet (PoE)	802.3 at (PoE+)

Available variants

ArtNr.	Bezeichnung	Unique
IGP-1061	10-Port L2 Man.Gigabit PoE Ind. Switch 802.3AT/AF/BT PoE, DIN Rail -40°C to 75°C	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

