

DATASHEET

Hilbert 8-Port Industrial PoE Smart Lite Gigabit Switch



General data

- 8 PoE-Plus Gigabit Ethernet ports with PoE watchdog
- IEEE 802.3af/at PoE compliant to simplify deployment and installation
- 1000Mbps full duplex, 10/100Mbps full/half duplex, auto-negotiation, auto-MDI/MDIX
- Supports 4K MAC address auto-learning and auto-aging
- 9K Jumbo Frames to increase data transfer rates
- IP multicast filtering through IGMP Snooping V1 / V2
- 802.1Q Tag-based VLAN enables network segmentation to improve performance and security
- IEEE 802.1p QoS with 4 priority queues
- Supports storm control for unknown unicast/broadcast/multicast
- Minimizes carbon footprint with energy efficient technology (IEEE 802.3az)
- Operating temperature range from -40°C to 75°C
- 4KV surge protection, 6KV contact/8KV air ESD protection
- Supports DIN rail installation
- Web-based Smart Lite real-time management
- Supports LevelOne IP Locator for easier IP management.

The LevelOne IGS-2108P Hilbert 8-Port Industrial Gigabit PoE Smart Lite Switch is a new generation Ethernet switch that offers powerful PoE functionality and ease of use, enabling Ethernet services cost-effectively over copper connections. The IGS-2108P offers 8 (10M/100M/1G) RJ45, of which 8 are PoE+ (support 802.3at/af) ports. to enable high-speed networks in mission-critical environments. With industrial standard DIN rail mounting and highly visible

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Hilbert 8-Port Industrial PoE Smart Lite Gigabit Switch

status LEDs, the switch provides easy monitoring of port connections. With the new LevelOne IP Locator, the simple switch discovery software, all Hilbert series switches can be searched and information about the switch and IP configuration can be displayed. It is compatible with the most common Windows and Mac operating systems. The LevelOne IGS-2108P offers high hardware performance and environmental flexibility for businesses. The IGS-2108P is ideal for easy management, optimal usability and lower total cost of ownership.

General

Color: Black

Features

L2 switching features

1. IGMP snooping

- Supports IGMP snooping
- Supports 128 groups

2. Link Aggregation

- Supports static link aggregation
- Supports 8 groups of aggregation, up to 4 ports per group

3. Port mirroring

- One-to-one
- Many-to-Many

4. Support port isolation, port grouping

VLAN

- Supports up to 32 VLANs (out of 4K VLAN IDs)
- Supports Port VLAN and 802.1Q VLAN
- Supports Port-based/802.1p/DSCP priority

QoS

- Support 4 priority queues
- Port Speed Limit
- Storm control

Administration

- Web-based Graphic User Interface (GUI)
- Supports LevelOne IP Locator for easier IP management.

Miscellaneous

Data rate Gigabit Ethernet

PoE power budget 112.00 watts

PoE Supported Yes

Fanless Yes

Manageable Yes

Series HILBERT series

Grade industrial

Others

Approvals and Compliance

- CE
- UKCA

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Hilbert 8-Port Industrial PoE Smart Lite Gigabit Switch

- FCC Part 15, Subpart B Class B
- RoHS
- Operating humidity 10% RH ~ 90% RH
- Operating temperature -40°C ~ 75°C
- Storage humidity 5% RH ~ 95% RH
- Storage temperature -40°C ~ 85°C

Scope of delivery

- IGS-2108P
- Power Terminal Block
- Din rail mount kit
- Quick Installation Guide
- Declaration of Conformity

Performance

Switching capacity 16 Gbps

Physical Specifications

Dimensions (W x D x H) 153 x 114 x 38 mm

Product weight (kg) 0.49 kg

System specifications

Acoustic noise (dB) 0 dB (A)

Micro switch LOOP, VLAN ON/OFF

Flash memory size 2 MB

Packet forwarding rate 11,904 Mpps

Heat dissipation 40.94 (Btu/H)

Indicator Power, Link/Act

Jumbo frames (KB) 9 KB

MAC address table 4K

Fastening DIN rail mount

MTBF 43,800 hrs

Packet buffer 1.5 Mbits

Pin assignment and polarity 1/2 (+), 3/6 (-)

Port Configuration 8x 10/100/1000 Mbps PoE+ copper ports

Energy consumption 120 W

Input voltage redundant dual DC 12V/24V/48V

Power supply VDC 44~57V

Standards

- IEEE 802.3 10-BASE-T (Ethernet)
- IEEE 802.3u 100-BASE-TX (Fast Ethernet)
- IEEE 802.3ab 1000BASE-T (Gigabit Ethernet)
- IEEE 802.3x Flow Control (full-duplex flow control)
- IEEE 802.3af Power over Ethernet
- IEEE 802.3at Power over Ethernet Plus
- IEEE 802.3az: Energy Efficient Ethernet

Technical properties

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

Hilbert 8-Port Industrial PoE Smart Lite Gigabit Switch

Gigabit Ethernet	True
Manufacturer	LevelOne
Mounting method	DIN rail (top hat rail)
Number of ports 10/100/1000 Mbps RJ45	8
Power over Ethernet (PoE)	802.3 at (PoE+)

Available variants

ArtNr.	Bezeichnung	Unique
IGS-2108P	Hilbert 8-Port Industrial PoE Smart Lite Gigabit Switch	Unique

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

