

DATASHEET

INFRALAN® 1-Port Frame Set, RAL9010, for all INFRALAN® Keystone Moduls



General data

To accommodate all INFRALAN® RJ45 Keystone modules
 Frame set in 1-port, 2-port or 3-port
 40° outlet
 Outer ring 80x80mm and central plate 50x50mm according to DIN49075
 Compatible with any switch range with the adapter plate of the switch range manufacturer
 Separate earthing latch for Faston 6.3mm blade receptacle
 With dust protection flaps and integrated labelling field

Technical properties

Assembly arrangement	Frame set
Connection unit	TAE

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

DATASHEET

INFRALAN® 1-Port Frame Set, RAL9010, for all INFRALAN® Keystone Moduls

Design-compatible	With manufacturer's adapter plate
Halogen free	No
Imprintable label	with indication plate
Material	Metal
Mounting method	Flush mounted (plaster)
Receptacle for	Keystone
Support ring	True
Temperature	0 - 60° °C
Type of fastening	mounting with screw
With dust cover	True
With hinged lid	True
With imprint	False

Available variants

ArtNr.	Bezeichnung	Colour	Depth of device	Height of device	RAL-number (similar)	Suitable for number of connectors	Width of device	With buses/couplings
IMT-01-RK-WS-KP	INFRALAN® 1-Port Frame Set, RAL9010, for all INFRALAN® Keystone Moduls	white	17.45 mm	80 mm	9010	1	80 mm	False

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 17-09-2026 . Technical changes reserved.

