

DATASHEET

IP67 Receptacle, M20, USB2.0, F-M, A-A, 0.5m



General data

IP67 mounting socket for mounting in distribution boxes with M25 cut-out

With pre-installed USB2.0 Jack/Jack A-A cable

Material: brass

With dust cap

Technical properties

Connection type connection 1	jack
Connection type connection 2	Stecker
Dust cover	True
Model	panel socket, 0.5m
Number of poles connection 1	4
Number of poles connection 2	4
Suitable for degree of protection (IP)	IP67
Type of connector connection 1	USB-A
Type of connector connection 2	USB-A
Type of housing	Brass nickel-plated
Type of locking	M20

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.



DATASHEET

IP67 Receptacle, M20, USB2.0, F-M, A-A, 0.5m

Available variants

ArtNr.	Bezeichnung	Colour	Length
IP67EBUSBA-A0,5FL	IP67 Receptacle, M20, USB2.0, F-M, A-A, 0.5m	grey	0.5 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 24-09-2026 . Technical changes reserved.

