DATASHEET

IP67 Receptacle, M20, USB2.0, F-M, A-A, service port, guy rope, 0.5m



General data
IP67 panel socket for installation in distributor boxes with M25 cut-out. With built-in USB2.0 socket / plug A-A cable Material: brass With captive dust protection cap

Technical properties	
Connection type connection 1	jack
Connection type connection 2	Plug
Dust cover	Non-losable (service)
Model	panel socket, 0.5m
Number of poles connection 1	4
Number of poles connection 2	4
Suitable for degree of protection (IP)	IP67
Type of connector connection 1	USB-A
Type of connector connection 2	USB-A
Type of housing	Nickel-plated brass
Type of locking	M20

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

IP67 Receptacle, M20, USB2.0, F-M, A-A, service port, guy rope, 0.5m

Available variants			
ArtNr.	**Bezeichnung**	**Colour**	**Length**
IP67EBUSBA-A0,5FLHS	IP67 Receptacle, M20, USB2.0, F-M, A-A, service port, guy rope, 0.5m	grau	0.5 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION