

DATASHEET

Industrial PoE Media Converter, 1 x 100/1000 SFP, 1x 100/1000T RJ45 with PoE++



General data

1x 60W PoE Injector compatible with IEEE802.3at/af
 Wide range of operation voltage 12 .. 57 V DC
 Auto-MDI/MDI-X function
 Dual Rate SFP Slot
 Redundant power supply input
 Temperature range -40°C .. +75°C
 Rugged metal housing, EMV-secure, protection class IP30
 DIN-Rail or wall mounting possible
 Suitable DIN-Rail power supply: NDR-75-48

Technical properties

Construction type	Single device
Degree of protection	IP30
Depth	110.0 mm
Fast Ethernet	True
Gigabit Ethernet	True
Height	135.0 mm
Managed	False
Manufacturer	CTS
Mode	MM or SM
Power over Ethernet	True
Suitable for 19 inch mounting	False
Type	PoE+
Width	36.0 mm

Available variants

ArtNr.	Bezeichnung	Max. PoE power	Rail mounting possible
IPC-3012-POE++	Industrial PoE Media Converter, 1 x 100/1000 SFP, 1x 100/1000T RJ45 with PoE++	60 W	True

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 21-09-2026 . Technical changes reserved.

