


DATASHEET

INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 5m, grey



General data

The S/FTP shielding reliably protects against interference and ensures good signal quality. Because it is a Cat.6A (TIA) network cable, it supports a frequency range of up to 500MHz, which provides high data transmission performance.

- Increase interference immunity in electromagnetically charged environments – double shielding (S/FTP) improves EMC reserve, reduces susceptibility to radiation and stabilizes transmission in parallel cable routing.
- Cover fire protection requirements in compliance with standards – flame-retardant cable behaviour according to IEC60332-1 reduces the spread of fire in the event of a fault and supports compliance with common installation specifications.
- Increased safety in the event of a fire – low smoke generation after IEC61034 helps to keep escape routes as low in smoke as possible in the event of a fire, and the halogen-free materials according to IEC60754-2 reduce the development of corrosive fire gases.

Product Description

The S/FTP patch cable has a double shield that effectively minimizes electromagnetic interference. It can be used in a temperature range of -20 – 60 °C. The patch cable has an IP20 rating. The LSZH jacket is halogen-free and low-smoke. In the event of a fire, it minimizes smoke development and increases indoor safety.

Technical details

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 5m, grey

- Cat.6A (TIA)
- Connector: RJ45 8(8) to RJ45 8(8) with RJ45 connectors
- Shielding: S/FTP cable with 4x2 x AWG26
- Cable shape: round
- Pin assignment: 1:1 according to TIA/EIA 568B
- Gold-plated contacts
- Sheath: LSZH sheath material
- Outer diameter: 6.0 mm
- With an injected anti-kink grommet
- Fire protection: flame-retardant according to IEC60332-1, low-smoke according to IEC61034, halogen-free according to IEC60754-2
- Degree of protection: IP20
- With a 360° umbrella attachment
- With locking lever protection
- Mating cycles: ≥750
- Brand: INFRALAN

Technical properties	
AWG-size	26
Allocation	acc. TIA/EIA 568B
Anti-kink sleeve	moulded-on
Area of Application	Industrial Ethernet
Bandwidth	500MHz
Cable construction	4x2
Cable shape	rund
Cable type	S/FTP
Category	6A (TIA)
Colour anti-kink sleeve	grey
Colour outer sheath	grey
Conductive shield	360° shield contact
Conductor Material	Copper
Connector type	RJ45 standard
Contacts	Gold plated
Fire retardant version	acc. IEC60332-1
Halogen free	acc. IEC60754-2
Harmonised Standard	EN 50575
Locking lever	True
Low smoke	acc. IEC61034
Material outer sheath	LSZH

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.



DATASHEET

INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 5m, grey

Mating cycles	≥750
Model	shielded
Oil resistant	no
Operating Temperature	-20 – 60 °C
Outer diameter of the cable	6.0 mm
Ozone resistance	No
Pin assignment	1:1
Printing	Cat.6A PREMIUM Patchcord U/UTP 4x2xAWG24/7 ISO/IEC11801 TIA/EIA-568-C.2 ***10Gigabit Ethernet***
Resistant to chemicals	False
Suitable for degree of protection (IP)	IP20
Test voltage	1000 (V DC, 1min) core/core und core/screen
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
UL approbated	False
UV resistant	no

Available variants

ArtNr.	Bezeichnung	Length
IPK-6A-U-TPE-GR-0025	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 0,25m, grey	0.25 m
IPK-6A-U-TPE-GR-0050	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 0,50m, grey	0.5 m
IPK-6A-U-TPE-GR-0100	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 1m, grey	1.0 m
IPK-6A-U-TPE-GR-0200	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 2m, grey	2.0 m
IPK-6A-U-TPE-GR-0300	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 3m, grey	3.0 m
IPK-6A-U-TPE-GR-0500	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 5m, grey	5.0 m
IPK-6A-U-TPE-GR-0750	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 7,5m, grey	7.5 m
IPK-6A-U-TPE-GR-1000	INFRALAN® RJ45 patch cord S/FTP, Cat.6A, TPE superflex, 10m, grey	10.0 m

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 08-10-2026 . Technical changes reserved.

