


# DATASHEET

## INFRALAN® Duplex Patchcable LC-LC OS2 G652D 1,5m LSZH 2mm yellow



### General data

The INFRALAN® LC fiber optic patch cables consist of defined components that are conform to structured cabling according to ISO/IEC 11801 and EN50173-x. The connectors used comply with IEC 61754-20 and meet the quality class B/2 according to IEC 61753-1 for the singlemode version and the quality class A/1 according to IEC 61753-122-2 for the multimode versions. The assembled patch cable has a halogen-free and flame-retardant sheath that complies with IEC 60754-2, IEC 60332-1 and IEC 61034 standards.

#### Application:

- Connecting active components
- Connecting passive components
- Connection of active connection elements
- Industrial cable connections
- subscriber connections

#### Delivery:

The INFRALAN® LC fiber optic patch cable is packed in a polybag containing a measurement report and clips for coding. Furthermore, the fiber is marked on the outer sheath with the INFRALAN® logo.

### Technical properties

|                  |        |
|------------------|--------|
| Anti-kink sleeve | put-on |
|------------------|--------|

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

# DATASHEET

## INFRALAN® Duplex Patchcable LC-LC OS2 G652D 1,5m LSZH 2mm yellow

|                                |                                                                            |
|--------------------------------|----------------------------------------------------------------------------|
| Bend optimized fiber           | no                                                                         |
| Cable structure                | Duplex                                                                     |
| Cable type                     | I-V(ZN) H                                                                  |
| Cable Ø                        | 2 mm                                                                       |
| Category                       | OS2 G652D                                                                  |
| Colour outer sheath            | yellow                                                                     |
| Fibre type                     | Single mode 9/125                                                          |
| Flame retardant                | acc. to IEC 60332-1-2                                                      |
| Halogen free                   | acc. to IEC 62821                                                          |
| Insertion loss 1310nm          | ≤0,15 dB                                                                   |
| Low smoke                      | acc. to IEC 61034                                                          |
| Material outer sheath          | LSZH                                                                       |
| Min. Bending radius (Dynamic)  | 20xOD mm                                                                   |
| Min. Bending radius (Static)   | 10xOD mm                                                                   |
| Number of fibres               | 2                                                                          |
| Operating Temperature          | -20 - 60 °C                                                                |
| Packaging                      | EFB-Electronics poly bag (resealable)                                      |
| Reinforcement                  | Aramid                                                                     |
| Return loss 1550nm             | ≥45 dB                                                                     |
| Return loss 1310nm             | ≥45 dB                                                                     |
| Scope of delivery              | 1x Patchcable, 2x Duplex Clip, 1x Measurement Report, 1x Information Sheet |
| Storage Temperature            | -20 - 70 °C                                                                |
| Type of connector connection 1 | LC                                                                         |
| Type of connector connection 2 | LC                                                                         |

### Available variants

| ArtNr.               | Bezeichnung                                                      | Length | Length tolerance |
|----------------------|------------------------------------------------------------------|--------|------------------|
| IPL-DR-LCULCU-2-0050 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 0,5m LSZH 2mm yellow | 0.5 m  | ±5 %             |
| IPL-DR-LCULCU-2-0100 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 1m LSZH 2mm yellow   | 1.0 m  | ±5 %             |
| IPL-DR-LCULCU-2-0150 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 1,5m LSZH 2mm yellow | 1.5 m  | ±5 %             |
| IPL-DR-LCULCU-2-0200 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 2m LSZH 2mm yellow   | 2.0 m  | ±5 %             |

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



# DATASHEET

## INFRALAN® Duplex Patchcable LC-LC OS2 G652D 1,5m LSZH 2mm yellow

|                      |                                                                  |        |      |
|----------------------|------------------------------------------------------------------|--------|------|
| IPL-DR-LCULCU-2-0300 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 3m LSZH 2mm yellow   | 3.0 m  | ±5 % |
| IPL-DR-LCULCU-2-0500 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 5m LSZH 2mm yellow   | 5.0 m  | ±5 % |
| IPL-DR-LCULCU-2-0750 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 7,5m LSZH 2mm yellow | 7.5 m  | ±5 % |
| IPL-DR-LCULCU-2-1000 | INFRALAN® Duplex Patchcable LC-LC OS2 G652D 10m LSZH 2mm yellow  | 10.0 m | ±5 % |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

