

DATASHEET

INFRALAN® Splicebox sliding version LC, 12 stripped pig-tails/ 6 adapter, OM3



General data

Completely equipped INFRALAN® splice box with adapter and through-dyed pigtails

The LC Pigtails are stripped off and inserted into the splice cassette

Measurement protocols of LC Pigtails are stored in the box

Metal housing depth adjustable (45mm) via 19" mounting bracket

All versions of the splice box are supplied with 24 coupling openings and fitted with blind inserts if the number of used ports is reduced.

Rear cable entry with 2x M20 openings on each side. The M20 openings can also be made laterally by replacing the opening plate with an angle plate (SB-A-GR-WINKEL). In addition, there is a central cable entry for 20x Simplex cables (up to 4.3mm).

incl. 1 x PG16

6 x self-adhesive fiber guides

Technical properties

Adapter material	Plastic adapter
Adapters	LC-Duplex
Depth	244.0 mm
Fibre class	OM3
Fibre type	Multimode 50/125
Height	44.5 mm

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.



DATASHEET

INFRALAN® Splicebox sliding version LC, 12 stripped pig-tails/ 6 adapter, OM3

Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Pigtails prepared	stripped
Sliding	sliding version
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	True

Available variants

ArtNr.	Bezeichnung	Colour	Pigtail	Type of connector external	With number of couplings/adapters	RAL-number	Type of connector interior	Adapter colour
ISB-LCDU-06-3-GR-ABA	INFRALAN® Splicebox sliding version LC, 12 stripped pigtails/ 6 adapter, OM3	grey	12 x LC	LC-Duplex	6	7035	LC-Duplex	aqua
ISB-LCDU-06-3-SW-ABA	INFRALAN® Splicebox sliding version LC, 12 stripped pigtails/ 6 adapter, OM3	black	12 x LC	LC-Duplex	6	9005	LC-Duplex	aqua
ISB-LCDU-24-3-GR-ABA	INFRALAN® Splicebox sliding version LC, 48 stripped pigtails/ 24 adapter, OM3	grey	48 x LC	LC-Duplex	24	7035	LC-Duplex	aqua

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 18-09-2026 . Technical changes reserved.

