DATASHEET

INFRALAN® Splicebox sliding version 24x LC-Duplex unequipped, grey





General data

INFRALAN® splice box unequipped, extendable for 24 x LC duplex, 1U 19". Front panel to accommodate max. 24 LC duplex adapters. Depth adjustable metal housing with mounting possibility for up to 4 splice cassettes. At the rear side 2 holders each for M20 and M25 cable glands, as well as two oblong holes for cables. Installation via 19" mounting bracket. Delivery including front panel with 24 cut-outs.

Technical properties

Depth	244.0 mm
Height	44.5 mm
Mounting method	482.6 mm (19 inch) mounting
Number of height units	1 U
Sliding	sliding
Width	483.0 mm
With front plate	True
With housing	True
With pigtails	False

Available variants

ArtNr.	Bezeichnung	Colour	RAL-number
ISB-LCDU-24-GR	INFRALAN® Splicebox sliding version 24x LC-Duplex unequipped, grey	grey	7035

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 02-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION