

# DATASHEET

## INFRALAN® Distribution Panel 19" 1U, 24-Port shifted, ANEXT optimized, black



### General data

For holding of modules in keystone format  
Inclusive cable management  
Labeling fields with transparent cover  
Strain relief via cable tie  
Delivery without modules

### Technical properties

|                                  |             |
|----------------------------------|-------------|
| Depth                            | 125.0 mm    |
| EMC-version                      | False       |
| Height                           | 44.45 mm    |
| Material                         | Metal       |
| Number of height units           | 1 U         |
| Temperature Range (Operation)    | -10 – 60 °C |
| Type of plug-in connector system | Keystone    |
| Width                            | 482.6 mm    |
| With buses/couplings             | False       |

### Available variants

| ArtNr.        | Bezeichnung                                                                  | Colour | Number of connector holes | Suitable for adapter | Assembly | RAL number | Note                                    |
|---------------|------------------------------------------------------------------------------|--------|---------------------------|----------------------|----------|------------|-----------------------------------------|
| IVF-24-SW-UTP | INFRALAN® Distribution Panel 19" 1U, 24-Port shifted, ANEXT optimized, black | Black  | 24                        | Keystone             | Without  | 9005       | Keystone Ports with shifted arrangement |

### Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



# DATASHEET

INFRALAN® Distribution Panel 19" 1U, 24-Port shifted,  
ANEXT optimized, black

regulatory requirements.

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.



EFB-Elektronik GmbH  
Striegauer Straße 1  
33719 Bielefeld

fon: +49 521 40 41 8-0  
fax: +49 521 40 41 8-50

info@efb-elektronik.de  
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG  
WE CARE FOR CONNECTION

