DATASHEET

INFRALAN® Distribution Panel 19" 1U, 24-Port shifted, ANEXT optimized, black



General data

For holding of modules in keystone format
Inclusive cable management
Labeling fields with transparent cover
Strain relief via cable tie
Delivery without modules

Technical properties

Depth	125.0 mm
EMC-version	False
Height	44.45 mm
Material	Metal
Number of height units	1 U
Temperature Range (Operation)	-10 – 60 °C
Type of plug-in connector system	Keystone
Width	482.6 mm
With buses/couplings	False

Available variants

ArtNr.	Bezeichnung	Colour	Number of connector holes	Suitable for adapter	Assembly	RAL number	Note
IVF-24-SW-UTP	INFRALAN® Distribution Panel 19" 1U, 24-Port shifted, ANEXT optimized, black	schwarz	24	Keystone	Without	9005	Keystone Ports with shifted arrangement

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and

This datasheet was created automatically on 11-11-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de