

DATASHEET

Earthing Bar for Network Cabinets 42U, Vertical, incl. 12 x Busbar Clamp



General data

For vertical installation in 42U network cabinets Classic/PRO

Mounting via supporting insulators on the sidely round holes of the 19" profiles (PRO: please use rear lateral raster holes)

Mountable also in combination with vertically blind panels

For mounting in server cabinets the installation of an additional 19" profile is recommended

Scope of delivery: copper earthing bar 1800 x 15 x 5 mm, 12 x busbar terminal 1.5 .. 16 mm², 4 x supporting insulator, 8 x thread bolt M6 x 25, 8 x washer, 8 x nut M6, self-locking

Technical properties

Application	Network cabinet
Cabinet Series	Classic

Available variants

ArtNr.	Bezeichnung	Mounting method
K3930V42	Earthing Bar for Network Cabinets 42U, Vertical, incl. 12 x Busbar Clamp	Screwing

Note on Intended Use

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.



DATASHEET

Earthing Bar for Network Cabinets 42U, Vertical, incl. 12 x Busbar Clamp

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 11-09-2026 . Technical changes reserved.

